

HNC-150BE-L-BLH

Sushi case with LED lighting, left sided

MODELS AVAILABLE

☐ HNC-120BE-L-BLH ☐ HNC-120BE-R-BLH ☐ HNC-150BE-R-BLH

M HNC-150BE-L-BLH ☐ HNC-180BE-L-BLH

☐ HNC-210BE-L-BLH ☐ HNC-210BE-R-BLH ☐ HNC-180BE-R-BLH



Powered by R600a Natural Refrigerant, energy efficient and sustainable, with a GWP = 3.



PRODUCT SERIES: HNC ITEM NUMBER: S053-C174

This Hoshizaki HNC-150BE-L-BLH is a Sushi case with LED lighting, left-sided. Our line of refrigerated display cases combines innovative features with a modern and elegant design, and are configured to highlight and preserve the freshness of even the most delicate fish

The range is designed to maintain the most natural level of humidity and food-safe temperatures, even during peak serving times with frequent door openings.

Airflow

The airflow created by the refrigeration effect of the evaporator is smooth and diffused, without forced air-circulation, which would cause dehydration and weight loss, resulting in swift deterioration of the fish or other perishable displayed food.

Temperature Control

One of the strikingly simple solutions for easy and fast temperature control: the inside wave shaped ABS trays can be flipped face up or down to allow more or less contact of the food with the cold trays. This way the cooling impact can be adjusted. A thermometer inside the cabinet helps you to monitor the inside temperature at all times.

Attractive Display

The tubular-shaped evaporator absorbs the heat continuously. Condensation freezes on its external surface, maintaining an attractive frost layer with no dripping. This model is equipped with LED lighting that can be turned on and off as needed.

Convenience

The practical anti-slip top is ideal to place serving dishes. The condensing unit of all our models sits either on the right- or left-hand side, with the outflow of air positioned on the sides away from the operator.

Easy Cleaning


The sliding door with 150mm height and the lightweight ABS trays with a wave-shaped profile are easily disassembled and removed for daily cleaning.













EXTERIOR FINISH Clear Glass, ABS Plastic, **PVC Plastic**

Refrigerant: R600a / 35g

OPERATING CONDITIONS LIMITATIONS

- Ambient temperature range: 10°C / 30°C
- Voltage range: rated voltage ±6%

MODEL	Temperature retention (°C)	Net capacity (I)	Electric connection	Electrical circuit breaker protection (A)	Electrical consumption power factor 60% (W)
HNC-150BE-L-BLH	5	57	1/220-240V/50Hz	6	145

TECHNICAL CERTIFICATIONS



For more information visit our website at www.hoshizaki-europe.com Hoshizaki Europe B.V. retains the right to change products and their specifications without prior notice.

HOSHIZAKI UK

2 The Technology Centre London Road Swanley, Kent BR8 7AG United Kingdom

T. +44 (0)845 456 0585 uksales@hoshizaki.uk www.hoshizaki.uk



LEADING NATURALLY

ITEM

HNC-150BE-L-BLH Sushi case with LED lighting, left sided



HOSHIZAKI DWER SWITCH


- Relative humidity exceeding 60% may result in excessive condensation on the exterior.
 The food temperature is controllable by turning over the food mounts.
 Product Code: S052-C174

11 -141	TroumEditi Codificor Circinodos			
MODEL	HNC-120BE-R-BLH			
POWER SUPPLY	1 Phase 220-240V 50Hz Capo	icity: 0.39kVA (1.63A)		
AMPERAGE	Rated: 1.0A Starting:	6A		
ELECTRIC CONSUMPTION	140W (Power Factor: 58	3%)		
HEAT REJECTION	410W			
PULL DOWN TIME	Approx. 30min.	Measured 20 mm above		
(10°C)	(Ambient Temp. 30°C, No Load)	the food mount (normal		
SATURATION	Approx. 5°C	position) located at the		
TEMPERATURE	(Ambient Temp. 30°C, No Load) interior bottom center			
POWER CORD	2.4m			
EFFECTIVE CAPACITY	431-			
OUTSIDE DIMENSIONS	122			
	1200mm(W) × 345mm(D) × 270mm(H)			
INSIDE DIMENSIONS	845mm(W) × 288mm(D)[Floor] × 157mm(H)			
EXTERIOR	Clear Glass, ABS Plastic, PVC Plastic			
INTERIOR	Clear Glass, ABS Plastic, Stainless Steel			
INSULATION	Polyurethane Foam			
INSULATION FOAM BLOWING AGENT	HFO-1233zd(E)			
DOOR	Sliding Glass × 2 [431mm(W) × 172mm(H)]		
REFRIGERATION SYSTEM	Convection Cooling			
DEFROST SYSTEM	N/A			
COMPRESSOR	Hermetic 110W			
CONDENSER	Fin and Tube type, Cooling Fan Motor provided			
EVAPORATOR	(Upper) Tube Type, (Lower) Pipe on Sheet Type			
REFRIGERANT	R600a/32g			
ELECTRIC CIRCUIT	Earth Leakage Circuit Breaker (with Overcurrent Protector) 15A			

Hoshizaki Counter Showcase











SHIPPING SPECIFICATIONS

MODEL	Net equipment dimensions		Crated dimensions		
	W x D x H (mm)	Net weight (kg)	W x D x H (mm)	Gross weight (kg)	Volume (m³)
HNC-150BE-L-BLH	1500 x 345 x 270	37	1580 x 415 x 517	52	0.32

ACCESSORIES

- Food mount (large) x 3
- Food mount (small) x 1
- Drain hose x 1



Hoshizaki Belgium: Hoshizaki Denmark: Hoshizaki Deutschland: Hoshizaki France: Hoshizaki Iberia: Hoshizaki Italia: Hoshizaki Middle East:

info@hoshizaki.be info@hoshizaki.dk info@hoshizaki.de info@hoshizaki.fr info@hoshizaki.es info@hoshizaki.it sales@hoshizaki.ae

Hoshizaki Netherlands: Hoshizaki Norge: Hoshizaki United Kingdom: Hoshizaki Sverige: Export Countries: Other countries:

info@hoshizaki.nl info@hoshizaki.no uksales@hoshizaki.uk orderSE@hoshizaki.dk sales@hoshizaki.nl sales@hoshizaki.nl